

AUDAC WS524



GENERAL FEATURES

- Speaker with line transformer – suitable for 100V system
- Two-way speaker
- Quick and easy installation thanks to suitable design for ceiling floor
- DC Blocking Card can be mounted into the speaker. (for line supervise)
- Standard white colour
- ABS Speaker

AUDAC WS524 two-way square ceiling floor type speaker is an imported product and produced as suitable for ceiling floors. These speakers which have been used especially in general sound and emergency announcement systems are called sheetrock and flush mounted as well. It has 3 stages with line transformer that is suitable for 100V principle. It has 6-12-24W power options.

AUDAC WS524 and other transformer speakers are used in hotels, residents, hospitals, shopping malls, private and public schools, universities, prisons, court buildings, chain stores, factories, industrial facilities, mosques, praying halls, restaurants, cafes etc. in public address and voice alarm systems.

TECHNICAL SPECIFICATIONS

Speaker Type	5" - 2 way
Application Power (RMS)	6W-12W-24W / 8ohm 60W
Input Impedance	100Vrms - 8 ohm
Frequency Repl	60-20000 Hz
SPL @ 1mt, 1W	92-107 dB
Body Seperator	ABS
Color	Standard White
Relative Humidity	%80
Operating Temperature	-10°C ~ 50°C
Storage Temperature	-30°C ~ 70°C
Dimensions(mm)	Mounting Cut-out:145x145 Outer Diameter:180