

DENOX LSC6.5



GENERAL FEATURES

- Speaker with line transformer – suitable for 100V system
- Quick and easy installation thanks to suitable design for ceiling floor
- DC Blocking Card can be mounted into the speaker. (for line supervise)
- Standard black colour
- ABS Speaker

DENOX LSC6.5 BLK ceiling floor type speaker is an imported product and produced as suitable for ceiling floors. These speakers which have been used especially in general sound and emergency announcement systems are called sheetrock and flush mounted as well. It has double stages with line transformer that is suitable for 100V principle. It has 5W and 10W power options

DENOX LSC6.5 BLK and other transformer speakers are used in hotels, residents, hospitals, shopping malls, private and public schools, universities, prisons, court buildings, chain stores, factories, industrial facilities, mosques, praying halls, restaurants, cafes etc. in public address and voice alarm systems.

TECHNICAL SPECIFICATIONS

Speaker Type	6"
Application Power (RMS)	5W/10W
Input Impedance	100Vrms
Frequency Reply	90-16000 Hz
SPL @ 1mt, 1W	91 dB
Body Seperator	ABS
Color	Standard Black
Relative Humidity	%80
Operating Temperature	-10°C ~ 50°C
Storage Temperature	-30°C ~ 70°C
Dimensions(mm)	Mounting Cut-out:160 Outer Diameter:190