

DENOX STUDIO5



GENERAL FEATURES

- Speaker with line transformer – suitable for 100V system
- Suitable for walls and columns, quick and easy installation
- DC Blocking Card can be mounted into the speaker. (for line supervise)
- Black & white colour options
- ABS speaker

DENOX STUDIO5 astron series column type speaker is an imported product and produced as suitable for installation onto wall or column in case of no ceiling floor. This speaker which has been used especially in general sound and emergency announcement systems is produced as with line transformer that is suitable for 100V principle. Due to the fact that the speaker which has 25W power option is two-sided and tweeter, it is preferred in music broadcast applications

DENOX STUDIO5 and other transformer speakers are used in hotels, residents, hospitals, shopping malls, private and public schools, universities, prisons, court buildings, chain stores, factories, industrial facilities, mosques, praying halls, restaurants, cafes etc. in public address and voice alarm systems.

TECHNICAL SPECIFICATIONS

Speaker Type	8" Woofer 1" Tweeter
Application Power (RMS)	25W - 125W
Input Impedance	100Vrms / 8 ohm
Frequency Reply	30-22000 Hz
SPL @ 1mt, 1W	90 dB
Body Separator	Durable Polystyren
Color	White & Black
Relative Humidity	%80
Operating Temperature	-10°C ~ 50°C
Storage Temperature	-30°C ~ 70°C
Dimensions(mm)	355 x 272 x 210mm