

# PASHA PMIC2



## GENERAL FEATURES

- Active microphone unit
- Swan-neck & cardioid dynamic microphone
- Ding-dong bell
- Announcement switch and LED indicator
- Sound setting button for output level
- D-Sub connector for connection

PASHA PMIC2 two zonal microphone unit has been designed to make announcement in general speaker systems. PMIC active microphone has a characteristic of automatic music stopping. In addition, it can be used as line amplifier to raise sound signals on the line which has 500 metres long.

In addition that PMIC2 microphone unit is used in 2 zonal systems, it is used in multi-zonal systems to make announcement to all zones at the same time as well. Cardioid dynamic microphone which is in swan-neck shape provides ease of use to users. You can set the announcement sound level via the button on the microphone and send pre-announcement warning via ding-dong bell

## TECHNICAL SPECIFICATIONS

Supply Voltage	24Vdc (From the system preamplifier)
Input Current	80 mA max.
Output Level	1,5 Vrms
Frequency Range	80Hz - 14kHz
Sensibility	4mVrms
Harmonic Distortion	Less from %0,1
Relative Humidity	%85
Operating Temperature	-10°C ~ 50°C
Storage Temperature	-30°C ~ 70°C
Dimensions	105 x 175 x 40 mm
Weight	1 Kg.