

DENOX FOCUS6



GENERAL FEATURES

- Speaker with line transformer – suitable for 100V system
- Two-way speaker
- Quick and easy installation thanks to suitable design for ceiling floor
- DC Blocking Card can be mounted into the speaker. (for line supervise)
- Standard white colour
- ABS Speaker

DENOX FOCUS 6 two-way ceiling floor type speaker is an imported product and produced as suitable for ceiling floors. These speakers which have been used especially in general sound and emergency announcement systems are called sheetrock and flush mounted as well. It has 4 stages with line transformer that is suitable for 100V principle. It has 5-10-15-25Watt power options.

DENOX FOCUS 6 and other transformer speakers are used in hotels, residents, hospitals, shopping malls, private and public schools, universities, prisons, court buildings, chain stores, factories, industrial facilities, mosques, praying halls, restaurants, cafes etc. in public address and voice alarm systems.

TECHNICAL SPECIFICATIONS

Speaker Type	6" / 2-way
Application Power (RMS)	5W-10W-15W-20W / 8ohm 45W
Input Impedance	100Vrms
Frequency Reply	70-20000 Hz
SPL @ 1mt, 1W	85 dB
Body Seperator	ABS
Color	Standard White
Relative Humidity	%80
Operating Temperature	-10°C ~ 50°C
Storage Temperature	-30°C ~ 70°C
Dimensions(mm)	Mounting Cut-out:178 Outer Diameter:200