

# DENOX LSOC5



## GENERAL FEATURES

- Speaker with line transformer – suitable for 100V system
- Quick and easy installation thanks to surface mounted design
- DC Blocking Card can be mounted into the speaker. (for line supervise)
- Dustproof and shockproof
- Standard white colour

DENOX LSOC5 surface mounted ceiling type speaker is an imported product and produced as suitable for installation onto ceiling and cable tray in case of no ceiling floor. This speaker which has been used especially in general sound and emergency announcement systems is produced as with line transformer that is suitable for 100V principle. It has 3W-6W power options. You can check other speakers of ours if you need higher power.

DENOX LSOC5 and other transformer speakers are used in hotels, residents, hospitals, shopping malls, private and public schools, universities, prisons, court buildings, chain stores, factories, industrial facilities, mosques, praying halls, restaurants, cafes etc. in public address and voice alarm systems.

## TECHNICAL SPECIFICATIONS

Speaker Type	4.5"
Application Power (RMS)	3W-6W
Input Impedance	100Vrms
Frequency Reply	100-15000 Hz
SPL @ 1mt, 1W	92 dB
Body Seperator	ABS
Color	Standard White
Relative Humidity	%80
Operating Temperature	-10°C ~ 50°C
Storage Temperature	-30°C ~ 70°C
Dimensions(mm)	230 x 115mm